




  
**Cyberoam**<sup>®</sup>  
 Unified Threat Management

**Cyberoam CR25wi**

**Comprehensive Network Security with Wi-Fi  
 Access Point for Small and Remote Offices**



*“Gartner positions  
 Cyberoam UTM as a  
 “Visionary” in Magic  
 Quadrant for SMB  
 Multifunction  
 Firewalls”*


CR25wi offers high performance security over WLAN to Small Office-Home Office (SOHO) and Remote Office Branch Office (ROBO) users. It supports 802.11n/b/g wireless standards. Combined with security over wired networks offered by its range of UTM appliances, Cyberoam enables organizations to overcome the physical limitations of securely accessing network resources and offers more user flexibility, user productivity and lower network ownership costs.

Cyberoam's Layer 8 technology that treats user-identity as the 8th Layer or the HUMAN layer in the protocol stack, works even in WLAN environments, to allow identity-based security policies in dynamic IP environment.

Insecure WLANs are easily susceptible to unauthorized intrusion by outsiders and malware attacks. Cyberoam extends its set of security features over wired networks Firewall, VPN, Anti-Virus/Anti-Spyware, Intrusion Prevention System, Content Filtering, Bandwidth Management and Multiple Link Management over WLAN, securing organizations from threats of data leakage and malware attacks.



### User Identity-based Security Policy Controls



**Cyberoam's Layer 8 Technology treats  
 “User Identity” as the 8th Layer  
 in the protocol stack**

Cyberoam UTM offers security across  
 Layer 2-Layer 8 using Identity-based policies

## • Cyberoam UTM features assure Security, Connectivity, Productivity •



### Security

#### Network Security

- Firewall
- Intrusion Prevention System
- Wireless security

#### Content Security

- Anti-Virus/Anti-Spyware
- Anti-Spam
- HTTPS/SSL Content Security

#### Administrative Security

- Next-Gen UI
- iView- Logging & Reporting



### Connectivity

#### Business Continuity

- Multiple Link Management
- High Availability

#### Network Availability

- VPN
- 3G/WiMAX Connectivity

#### Future-ready Connectivity

- “IPv6 Ready” Gold Logo



### Productivity

#### Employee Productivity

- Content Filtering
- Instant Messaging Archiving & Controls

#### IT Resource Optimization

- Bandwidth Management
- Traffic Discovery
- Application Layer 7 Management

#### Administrator Productivity

- Next-Gen UI

# Specification

## Interfaces

10/100/1000 Ethernet Ports	4
Configurable	
Internal/DMZ/WAN Ports	Yes
Console Ports (RJ45/DB9)	1
USB Ports	1

## Built-in Wireless LAN

Wireless Standards	IEEE 802.11 n/b/g (WEP, WPA, WPA2, 802.11i, TKIP, AES, PSK, 802.1x EAP)
--------------------	---

Antenna Detachable 2x3 MIMO

Access Points Up to 8 bssid

Transmit Power (EIRP)  
11n HT40 : +17dBm  
11b CCK: +19dBm  
11g OFDM: +17dBm

Receiver Sensitivity  
-65dBm at 300Mbps  
-70dBm at 54Mbps 10% PER  
-86dBm at 11Mbps 8% PER

Frequency Range  
USA (FCC): 2.412GHz ~ 2.462GHz  
Europe (ETSI): 2.412GHz ~ 2.472 GHz  
Japan (TELEC): 2.412GHz ~ 2.483GHz

Number of Selectable Channels  
USA (FCC) - 11 channels,  
EU (ETSI) / Japan (TELEC) - 13 channels

Data Rate  
802.11n: up to 300Mbps,  
802.11b: 1, 2, 5.5, 11Mbps,  
802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps

## System Performance\*

Firewall throughput (UDP)	450 (Mbps)
Firewall throughput (TCP)	250 (Mbps)
New sessions/second	3,500
Concurrent sessions	130,000
168-bit 3DES/AES throughput	30/75 (Mbps)
Anti-Virus throughput	65 (Mbps)
IPS throughput	70 (Mbps)
UTM throughput	50 (Mbps)

## Stateful Inspection Firewall

- Layer 8 (User - Identity) Firewall
- Multiple Security Zones
- Access Control Criteria (ACC) - User - Identity, Source & Destination Zone, MAC and IP address, Service
- UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management
- Layer 7 (Application) Control & Visibility
- Access Scheduling
- Policy based Source & Destination NAT
- H.323, SIP NAT Traversal
- 802.1q VLAN Support
- DoS & DDoS Attack prevention
- MAC & IP-MAC filtering and Spoof prevention

## Gateway Anti-Virus & Anti-Spyware

- Virus, Worm, Trojan Detection & Removal
- Spyware, Malware, Phishing protection
- Automatic virus signature database update
- Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
- Customize individual user scanning
- Scan and deliver by file size
- Block by file types
- Add disclaimer/signature

## Gateway Anti-Spam

- Real-time Blacklist (RBL), MIME header check
- Filter based on message header, size, sender, recipient
- Subject line tagging
- IP address Black list/White list
- Redirect Spam mails to dedicated email address
- Image-based Spam filtering using RPD Technology
- Zero hour Virus Outbreak Protection
- IP Reputation-based Spam filtering

## Intrusion Prevention System

- Signatures: Default (3000+), Custom
- IPS Policies: Multiple, Custom
- User-based policy creation

- Automatic real-time updates from CRProtect networks
- Protocol Anomaly Detection
- DDoS attack prevention

## Web Filtering

- Inbuilt Web Category Database
- URL, keyword, File type block
- Categories: Default(82+), Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Schedule-based access control
- Custom block messages per category
- Block Java Applets, Cookies, Active X
- CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

## Application Filtering

- Inbuilt Application Category Database
- Application Categories: e.g. Gaming, IM, P2P, Proxy:11+
- Schedule-based access control
- Block
  - P2P applications e.g. Skype
  - Anonymous proxies e.g. Ultra surf
  - "Phone home" activities
  - Keylogger
- Layer 7 (Applications) & Layer 8 (User - Identity) Visibility

## Virtual Private Network

- IPsec, L2TP, PPTP
- Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication - Preshared key, Digital certificates
- IPsec NAT Traversal
- Dead peer detection and PFS support
- Diffie Hellman Groups - 1,2,5,14,15,16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points
- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support

## SSLVPN

- TCP/UDP Tunneling
- Authentication - Active Directory, LDAP, RADIUS, Cyberoam
- Multi-layered Client Authentication - Certificate, Username/Password
- User & Group policy enforcement
- Network access - Split and Full tunneling
- Browser-based (Portal) Access - Clientless access
- Lightweight SSL VPN Tunneling Client
- Granular access control to all the Enterprise Network resources
- Administrative controls - Session timeout, Dead Peer Detection, Portal customization
- TCP-based Application Access - HTTP, HTTPS, RDP, TELNET, SSH

## Instant Messaging (IM) Management

- Yahoo and Windows Live Messenger
- Virus Scanning for IM traffic
- Allow/Block Login
- Allow/Block File Transfer
- Allow/Block Webcam
- Allow/Block one-to-one/group chat
- Content-based blocking
- IM activities Log
- Archive files transferred
- Custom Alerts

## Wireless WAN

- USB port 3G and Wimax Support\*
- Primary WAN link
- WAN Backup link

## Bandwidth Management

- Application and User Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Multi WAN bandwidth reporting
- Category-based bandwidth restriction

## User Identity and Group Based Controls

- Access time restriction
- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth
- Schedule based P2P and IM Controls

## Networking

- Failover - Automated Failover/Failback, Multi-WAN failover, 3GModem failover
- WRR based load balancing
- Policy routing based on Application and User
- IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay
- Support for HTTP Proxy
- Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding
- Parent Proxy support with FQDN
- "IPv6 Ready" Gold Logo

## Administration & System Management

- Web-based configuration wizard
- Role-based access control
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
- Multi-lingual support: Chinese, Hindi, French, Korean
- Cyberoam Central Console (Optional)
- NTP Support

## User Authentication

- Internal database
- Active Directory Integration
- Automatic Windows Single Sign On
- External LDAP/RADIUS database integration
- Thin Client support - Microsoft Windows Server 2003 Terminal Services and Citrix XenApp
- RSA SecurID support
- External Authentication - Users and Administrators
- User/MAC Binding
- Multiple Authentication servers

## Logging/Monitoring

- Graphical real-time and historical monitoring
- Email notification of reports, viruses and attacks
- Syslog support
- Log Viewer - IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

## On-Appliance Cyberoam-iView Reporting

- Integrated Web-based Reporting tool - Cyberoam-iView
- 1000+ drilldown reports
- 45+ Compliance Reports
- Historical and Real-time reports
- Multiple Dashboards
- Username, Host, Email ID specific Monitoring Dashboard
- Reports - Security, Spam, Virus, Traffic, Policy violations, VPN, Search Engine keywords
- Multi-format reports - tabular, graphical
- Exportable formats - PDF, Excel
- Automated Report Scheduling

## IPsec VPN Client\*\*

- Inter-operability with major IPsec VPN Gateways
- Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
- Import Connection configuration

## Certification

- ICSA Firewall - Corporate
- Checkmark UTM Level 5 Certification
- VPNC - Basic and AES interoperability
- "IPv6 Ready" Gold Logo

## Compliance

- CE
- FCC

## Dimensions

H x W x D (inches)	1.7 x 6 x 9.1
H x W x D (cms)	4.4 x 15.3 x 23.2
Weight	2.3kg, 5.07 lbs

## Power

Input Voltage	100-240 VAC
Consumption	33.5W
Total Heat Dissipation (BTU)	114

## Environmental

Operating Temperature	5 to 40 °C
Storage Temperature	0 to 75 °C
Relative Humidity (Non condensing)	10 to 90%

\*Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.

\*\*Additional purchase required. \*3G card and modem details are not included. See <http://www.cyberoam.com> for supported USB devices.

## Toll Free Numbers

USA : +1-800-686-2360 | India : 1-800-301-00013  
APAC/MEA : +1-877-777-0368 | Europe : +44-808-120-3958