



## Cyberoam CR25i

### Comprehensive Network Security for Small and Remote Offices



### Cyberoam UTM

Cyberoam CR25i is the identity-based security appliance that works on Layer 8, delivering real-time protection against evolving external and internal threats to Small Office-Home Office (SOHO) and Remote Office-Branch Office (ROBO) users.

Small, remote offices with limited security like firewall, anti-virus are exposed to Internet threats. Cyberoam delivers comprehensive protection from malware, virus, spam, phishing, pharming and more. Its unique identity-based security protects users from internal threats that lead to data leakage. Cyberoam features include Stateful Inspection Firewall, VPN (SSL VPN & IPSec), Gateway Anti-Virus and Anti-Spyware, Gateway Anti-Spam, IPS, Content Filtering, Bandwidth Management, Multiple Link Management and can be centrally managed with Cyberoam Central Console.

### Identity-based Security in UTM

Cyberoam attaches the user identity to security, taking enterprises a step ahead of conventional solutions that bind security to IP-addresses. Cyberoam's identity-based security offers full business flexibility while ensuring complete security in any environment, including DHCP and Wi-Fi, by identifying individual users within the network-whether they are victims or attackers.

Features	Description	Benefits
<b>Stateful Inspection Firewall (ICSA Labs Certified)</b>	<ul style="list-style-type: none"> <li>Powerful stateful and deep packet inspection</li> <li>Fusion technology blends all the components of Cyberoam into a single firewall policy</li> <li>Prevents DoS &amp; flooding attacks from internal &amp; external sources</li> <li>Identity-based access control for applications like P2P, IM</li> </ul>	<ul style="list-style-type: none"> <li>Application layer protection</li> <li>Provides the right balance of security, connectivity and productivity</li> <li>Flexibility to set policies by user identity</li> <li>High scalability</li> </ul>
<b>Virtual Private Network</b>	<ul style="list-style-type: none"> <li>Threat Free Tunneling</li> <li>Industry standard: IPSec, SSL, L2TP, PPTP VPN</li> <li>VPN High Availability for IPSec and L2TP connections</li> <li>Dual VPNC Certifications - Basic and AES Interop</li> </ul>	<ul style="list-style-type: none"> <li>Safe and clean VPN traffic</li> <li>Secure connectivity to branch offices and remote users</li> <li>Low cost remote connectivity over the Internet</li> <li>Effective failover management with defined connection priorities</li> </ul>
<b>Gateway Anti-Virus &amp; Anti-Spyware</b>	<ul style="list-style-type: none"> <li>Scans HTTP, FTP, IMAP, POP3 and SMTP traffic</li> <li>Detects and removes viruses, worms and Trojans</li> <li>Access to quarantined mails to key executives</li> <li>Instant user identification in case of HTTP threats</li> </ul>	<ul style="list-style-type: none"> <li>Complete protection of traffic over all protocols</li> <li>High business flexibility</li> <li>Protection of confidential information</li> <li>Real-time security</li> </ul>
<b>Gateway Anti-Spam</b>	<ul style="list-style-type: none"> <li>Scans SMTP, POP3 and IMAP traffic for spam</li> <li>Detects, tags and quarantines spam mail</li> <li>Enforces black and white lists</li> <li>Virus Outbreak Protection</li> <li>Content-agnostic spam protection including Image-spam using Recurrent Pattern Detection (RPD™) Technology</li> </ul>	<ul style="list-style-type: none"> <li>Enhances productivity</li> <li>High business flexibility</li> <li>Protection from emerging threats</li> <li>High scalability</li> <li>Zero hour protection incase of virus outbreaks</li> <li>Multi-language and Multi-format spam detection</li> </ul>
<b>Intrusion Prevention System - IPS</b>	<ul style="list-style-type: none"> <li>Database of over 3000 signatures</li> <li>Multi-policy capability with policies based on default &amp; custom signatures, source and destination</li> <li>Prevents intrusion attempts, DoS attacks, malicious code, backdoor activity and network-based blended threats</li> <li>Blocks anonymous proxies with HTTP proxy signatures</li> <li>Blocks "phone home" activities</li> </ul>	<ul style="list-style-type: none"> <li>Low false positives</li> <li>Real-time Security in dynamic environments like DHCP and Wi-Fi</li> <li>Offers instant user-identification in case of internal threats</li> <li>Apply IPS policies on users</li> </ul>
<b>Content &amp; Application Filtering</b>	<ul style="list-style-type: none"> <li>Automated web categorization engine blocks non-work sites based on millions of sites in over 82+ categories</li> <li>URL Filtering for HTTP &amp; HTTPS protocols</li> <li>Hierarchy, department, group, user-based filtering policies</li> <li>Time-based access to pre-defined sites</li> <li>Prevents downloads of streaming media, gaming, tickers, ads</li> <li>Supports CIPA compliance for schools and libraries</li> </ul>	<ul style="list-style-type: none"> <li>Prevents exposure of network to external threats</li> <li>Blocks access to restricted websites</li> <li>Ensures regulatory compliance</li> <li>Saves bandwidth and enhances productivity</li> <li>Protects against legal liability</li> <li>Ensures the safety and security of minors online</li> <li>Enables schools to qualify for E-rate funding</li> </ul>
<b>Bandwidth Management</b>	<ul style="list-style-type: none"> <li>Committed and burstable bandwidth by hierarchy, departments, groups &amp; users</li> </ul>	<ul style="list-style-type: none"> <li>Prevents bandwidth congestion</li> <li>Prioritizes bandwidth for critical applications</li> </ul>
<b>Multiple Link Management</b>	<ul style="list-style-type: none"> <li>Security over multiple ISP links using a single appliance</li> <li>Load balances traffic based on weighted round robin distribution</li> <li>Link Failover automatically shifts traffic from a failed link to a working link</li> </ul>	<ul style="list-style-type: none"> <li>Easy to manage security over multiple links</li> <li>Controls bandwidth congestion</li> <li>Optimal use of low-cost links</li> <li>Ensures business continuity</li> </ul>
<b>On-Appliance Reporting</b>	<ul style="list-style-type: none"> <li>Complete Reporting Suite available on the Appliance</li> <li>Traffic discovery offers real-time reports</li> <li>Reporting by username</li> </ul>	<ul style="list-style-type: none"> <li>Reduced TCO as no additional purchase required</li> <li>Instant and complete visibility into patterns of usage</li> <li>Instant identification of victims and attackers in internal network</li> </ul>

# Specification

<b>Interfaces</b>			
10/100 Ethernet Ports	4	Browser-based (Portal) Access - Clientless access	Yes
10/100/1000 GBE Ports	-	Lightweight SSL VPN Tunneling Client	Yes
Configurable Internal/DMZ/WAN Ports	Yes	Granular access control to all the Enterprise Network resources	Yes
Console Ports (RJ45)	1	Administrative controls - Session timeout, Dead Peer Detection, Portal customization	Yes
SFP (Mini GBIC) Ports	-		
COM port	1		
USB ports	2		
<b>System Performance*</b>		<b>Bandwidth Management</b>	
Firewall throughput (Mbps)	100	Application and User Identity based Bandwidth Management	Yes
New sessions/second	2,200	Guaranteed & Burstable bandwidth policy	Yes
Concurrent sessions	130,000	Application & User Identity based Traffic Discovery	Yes
168-bit Triple-DES/AES throughput (Mbps)	30/75	Multi WAN bandwidth reporting	Yes
Antivirus throughput (Mbps)	30		
IPS throughput (Mbps)	60	<b>User Identity and Group Based Controls</b>	
UTM throughput (Mbps)	25	Access time restriction	Yes
		Time and Data Quota restriction	Yes
		Schedule based Committed and Burstable Bandwidth	Yes
		Schedule based P2P and IM Controls	Yes
<b>Stateful Inspection Firewall</b>		<b>Networking</b>	
Multiple Zones security with separate levels of access rule enforcement for each zone	Yes	Multiple Link Auto Failover	Yes
Rules based on the combination of User, Source & Destination Zone and IP address and Service	Yes	WRR based Load balancing	Yes
Actions include policy based control for IPS, Content Filtering, Anti virus, Anti spam and Bandwidth Management	Yes	Policy routing based on Application and User	Yes
Access Scheduling	Yes	DDNS/PPPoE Client	Yes
Policy based Source & Destination NAT	Yes	Support for HTTP Proxy	Yes
H.323 NAT Traversal	Yes	Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding	Yes
802.1q VLAN Support	Yes	Parent Proxy support with FQDN	Yes
DoS & DDoS Attack prevention	Yes		
<b>Gateway Anti-Virus &amp; Anti-Spyware</b>		<b>Administration &amp; System Management</b>	
Virus, Worm, Trojan Detection & Removal	Yes	Web-based configuration wizard	Yes
Spyware, Malware, Phishing protection	Yes	Role-based administration	Yes
Automatic virus signature database update	Yes	Multiple administrators and user levels	Yes
Scans HTTP, FTP, SMTP, POP3, IMAP, VPN Tunnels	Yes	Upgrades & changes via Web UI	Yes
Customize individual user scanning	Yes	Multi-lingual support: Chinese, Hindi	Yes
Self Service Quarantine area	Yes	Web UI (HTTPS)	Yes
Scan and deliver by file size	Yes	Command line interface (Serial, SSH, Telnet)	Yes
Block by file types	Yes	SNMP (v1, v2c, v3)	Yes
Add disclaimer/signature	Yes	Cyberoam Central Console	Yes
		Version Rollback	Yes
		NTP Server Support	Yes
<b>Gateway Anti-Spam</b>		<b>User Authentication</b>	
Real-time Blacklist (RBL), MIME header check	Yes	Local database	Yes
Filter based on message header, size, sender, recipient	Yes	Windows Domain Control & Active Directory Integration	Yes
Subject line tagging	Yes	Automatic Windows Single Sign On	Yes
IP address Black list/White list	Yes	External LDAP/RADIUS database Integration	Yes
Redirect spam mails to dedicated email address	Yes	User/MAC Binding	Yes
Image-based spam filtering using RPD Technology	Yes		
Zero hour Virus Outbreak Protection	Yes	<b>Logging/Monitoring</b>	
Self Service Quarantine area	Yes	Internal HDD	Yes
		Graphical real-time and historical monitoring	Yes
		Email notification of reports, viruses and attacks	Yes
		Syslog support	Yes
<b>Intrusion Prevention System</b>		<b>On-Appliance Reporting</b>	
Signatures: Default (3000+), Custom	Yes	Intrusion events reports	Yes
IPS Policies: Multiple, Custom	Yes	Policy violations reports	Yes
User-based policy creation	Yes	Web Category reports (user, content type)	Yes
Automatic real-time updates from CRProtect networks	Yes	Search Engine Keywords reporting	Yes
Protocol Anomaly Detection	Yes	Data transfer reporting (By Host, Group & IP Address)	Yes
Block		Virus reporting by User and IP Address	Yes
- P2P applications e.g. Skype	Yes	Compliance Reports	45+
- Anonymous proxies e.g. Ultra surf	Yes		
- "Phone home" activities	Yes	<b>VPN Client</b>	
- Keylogger	Yes	IPSec compliant	Yes
		Inter-operability with major IPSec VPN Gateways	Yes
		Supported platforms: Windows 98, Me, NT4, 2000, XP, Vista	Yes
		Import Connection configuration	Yes
<b>Content &amp; Application Filtering</b>		<b>Certification</b>	
Inbuilt Web Category Database	Yes	ICSA Firewall - Corporate	Yes
URL, keyword, File type block	Yes	VPNC - Basic and AES interoperability	Yes
Categories: Default(82+), Custom	Yes	Checkmark UTM Level 5 Certification	Yes
Protocols supported: HTTP, HTTPS	Yes		
Block Malware, Phishing, Pharming URLs	Yes	<b>Compliance</b>	
Custom block messages per category	Yes	CE	Yes
Block Java Applets, Cookies, Active X	Yes	FCC	Yes
CIPA Compliant	Yes		
Data leakage control via HTTP upload	Yes	<b>Dimensions</b>	
		H x W x D (inches)	1.97 x 8.86 x 8.07
		H x W x D (cms)	5.0 x 22.5 x 20.5
		Weight	2.1 kg, 4.62 lbs
<b>Virtual Private Network</b>		<b>Power</b>	
IPSec, L2TP, PPTP	Yes	Input Voltage	100-240 VAC
Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent	Yes	Consumption	24.8W
Hash Algorithms - MD5, SHA-1	Yes	Total Heat Dissipation (BTU)	85
Authentication - Preshared key, Digital certificates	Yes		
IPSec NAT Traversal	Yes	<b>Environmental</b>	
Dead peer detection and PFS support	Yes	Operating Temperature	5 to 40 °C
Diffie Hellman Groups - 1,2,5,14,15,16	Yes	Storage Temperature	0 to 70 °C
External Certificate Authority support	Yes	Relative Humidity (Non condensing)	5 to 95%
Export Road Warrior connection configuration	Yes	Cooling System - Fan	1
Domain name support for tunnel end points	Yes		
VPN connection redundancy	Yes		
Overlapping Network support	Yes		
Hub & Spoke VPN support	Yes		
<b>SSL VPN</b>			
TCP & UDP Tunneling	Yes		
Authentication - Active Directory, LDAP, RADIUS, Cyberoam	Yes		
Multi-layered Client Authentication - Certificate, Username/Password	Yes		
User & Group policy enforcement	Yes		
Network access - Split and Full tunneling	Yes		

\*Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.

## Toll Free Numbers

USA : +1-877-777-0368 | India : 1-800-301-00013  
 APAC/MEA : +1-877-777-0368 | Europe : +44-808-120-3958

Copyright © 1999 - 2009 Ellitecore Technologies Ltd. All rights reserved.  
 Cyberoam and Cyberoam logo are registered trademark of Ellitecore Technologies Ltd. Although Ellitecore has attempted to provide accurate information, Ellitecore assumes no responsibility for accuracy or completeness of information neither is this a legally binding representation. Ellitecore has the right to change, modify, transfer or otherwise revise the publication without notice. PL-10-95811-090131

